

Corrosion-resistant polycarbonate luminaires

IP65 luminaires with injection moulded polycarbonate body and frosted prismatic polycarbonate cover, both fire-retardant.

Applications: cold stores, printing works, water treatment plants and pump rooms, industrial process areas, shower rooms and toilet blocks.

- Smooth easy-clean lines
- Snug-fit polycarbonate cover clips (stainless steel option)
- Fast installation via external stainless-steel brackets preserves IP rating
- Factory fitted 4-core through wiring option (alternative configurations to special order)
- Suitable for external applications if mounted under a canopy
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit

Notes: For ambient temperatures below the stated minimum contact the Thorlux Technical department



Up to IP65

Up to 132.4 LL/CW

SMARTSCAN

Specification

Mounting	Surface	IP rating	Up to IP65
Max presence detection height	8 m		

Lighting

Optic	Frosted prismatic cover	Lumen output	3,700 lm - 9,535 lm
Efficacy	Up to 132.4 LL/CW		

Emergency data

Emergency lumen output	435 lm - 640 lm	Emergency type	Maintained
Emergency duration	3 hours	Battery specification	Nickel Metal Hydride (NiMH)

Power

LED power	23 W - 60 W	Circuit power	31 W - 72 W
-----------	-------------	---------------	-------------

LED characteristics


CRI	80+	Colour temperature	4000 K
Rated life (hours)	100 K - L70/B10		

Compliance



UKCA	Yes	CE	Yes
C-Tick (Aus)	Yes	D Mark	Yes
Food production standards	HACCP IFS	MOD compliance	JSP482 Chapter 8 Document for 'Category C' areas

Dimensions

Narrow Body



Wide Body





Click or scan here
View Thoroproof variants
using our online filtering tool



Information is correct as of 12 Mar 2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.