

## Retrofit kit for Dot luminaires

Energy saving, fast installation retrofit solution.

- 100,000 hour LED life expectancy
- Suitable for existing 28 W and 38 W, 452 mm diameter versions
- Significantly improved efficiency; power consumption more than halved compared with 38W 2D
- Easy to install
- Suitable for retrofit into existing standard, emergency and AutoTest Dot luminaire



## Lighting management

Emergency system	<b>AutoTest Emergency</b> <b>Non-emergency</b> <b>Standard Emergency</b>
------------------	--

## Lighting

Lumen Output (Multiple)	<b>Satin Sparkle 2500 lm / Opal 1865 lm</b>	Efficacy	<b>0 LL/CW</b>
Efficacy (Multiple)	<b>Up to Satin Sparkle 156.3 ll/cw / Opal 116.6 ll/cw</b>		

## Emergency data

Emergency Lumen Output	<b>Satin Sparkle 460 lm / Opal 340 lm</b>	Emergency type	<b>Maintained</b>
Emergency duration	<b>3 hours</b>	Battery specification	<b>Nickel Metal Hydride (NiMH)</b>

## Power

LED power	<b>13 W</b>	Circuit power	<b>16 W</b>
-----------	-------------	---------------	-------------

## LED characteristics

CRI	<b>80+</b>	Colour temperature	<b>4000 K</b>
Rated life (hours)	<b>100 K - L80/B10</b>		

## Compliance

UKCA	Yes	CE	Yes
C-Tick (Aus)	Yes	Energy efficiency class	<b>This product contains a light source of energy efficiency class B</b>

## Spares

Product code	Description	Weight
DOT15069	Satin sparkle effect polycarbonate cover	-



View the range

