

Retrofit kit for Prismalette Pro luminaires

Energy saving, fast installation retrofit solution



Up to 113.1 LL/CW

Lighting management

Lighting control system	Non-dimming	Emergency system	AutoTest Emergency Non-emergency SmartScan Emergency Standard Emergency
-------------------------	-------------	------------------	--

Lighting

Lumen output	1,535 lm - 2,035 lm	Efficacy	Up to 113.1 LL/CW
--------------	---------------------	----------	-------------------

Emergency data

Emergency lumen output	220 lm - 250 lm	Emergency type	Maintained
Emergency duration	3 hours	Battery specification	Nickel Metal Hydride (NiMH)

Power

LED power	12 W - 16 W	Circuit power	15 W - 18 W
-----------	-------------	---------------	-------------

LED characteristics

CRI	80+	Colour temperature	4000 K
Rated life (hours)	100 K - L80/B10		

Compliance

UKCA	Yes	CE	Yes
C-Tick (Aus)	Yes	Energy efficiency class	This product contains a light source of energy efficiency class B
SmartScan wireless standards compliance	Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724		



View the range

