
SmartScan Colour



Wireless manual colour control, switching and dimming of SmartScan ColourActive luminaires

Impact resistant manual control for SmartScan luminaires. 12 buttons providing On (Eco), Off, 5 fixed colour temperature levels and 5 fixed dimming levels.

- 12 buttons providing On (Eco), Off, 5 fixed colour temperature levels and 5 fixed dimming levels
- Mains (230 V) or battery powered versions available
- Communicates wirelessly with SmartScan luminaires
- Mains versions have additional wireless connectivity allowing control from the SmartScan App (iOS and Android)
- Requires a 35 mm deep single-gang back box (mains version only)
- Battery version is supplied complete with batteries and selfadhesive tape and can be mounted directly to the wall
- Multiple touch plates can be used to provide multi-point control
- Programmable using the SmartScan programmer





Compliance

SmartScan wireless standards compliance

Europe: EN 300 220-1 V2.4.1/ EN 301 489-3 V1.6.1. Australasia: ACMA 2014 Radio Communication Standard 2014. Thorlux Patented Wireless Technology - GB2575724

Dimensions



SmartScan Colour





Information is correct as of 24 Nov 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.