


LED area floodlights

IP66 wall or pole-mounted LED luminaire with aluminium cast body and wiring box with glass cover. Integral high-quality driver. Emergency, SmartScan and photocell options.

Applications include car parks, amenity areas, sports areas, and large open spaces.

- Strong high pressure die-cast LM6 aluminium body with clear toughened/safety glass cover
- Area or flood distribution options
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Universal bracket for wall or column mounting
- Photocell option
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit

Notes: Warmer colour temperatures available to special order



Up to IP66

IK08

Up to 141.0 LL/CW

SMARTSCAN

LED PROTECT

Specification

Mounting	Column Surface	IP rating	Up to IP66
Impact rating	IK08	Max presence detection height	8 m

Lighting

Optic	Clear cover	Lumen output	3,810 lm - 31,175 lm
Efficacy	Up to 141.0 LL/CW		

Emergency data

Emergency type	Maintained	Emergency duration	3 hours
Battery specification	Nickel Metal Hydride (NiMH)		

Power

LED power	31 W - 215 W	Circuit power	35 W - 234 W
-----------	--------------	---------------	--------------

LED characteristics


CRI	70+	Colour temperature	3000 K 4000 K
Rated life (hours)	100 K - L90/B10		

Compliance


UKCA	Yes	CE	Yes
C-Tick (Aus)	Yes		

Dimensions

Large Version



Small Version





Click or scan here
View Starbeam Plus variants
using our online filtering tool



Information is correct as of 22 Feb 2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.